

# TRUCKSTER XD™ Heavy Duty Utility Vehicle

## SPECIFICATIONS

Engine	Petrol	Diesel
Type	Kubota® 972EFI Petrol, 3-cylinder, 4-cycle, liquid cooled electronic fuel injection	Kubota® D1105 diesel, 3-cylinder, 4-cycle, liquid cooled
Horsepower*	25.2 kW (32.5 hp)	18.5 kW (24.8 hp)
Torque	70 Nm (51.6 ft-lbs)	71.67 Nm (52.7ft-lbs)
Air Cleaner	Donaldson® dry cartridge type with evacuator valve	
Fuel Capacity	26.5 L (7.0 gal.) unleaded	
Electrical System	60 amp, heavy duty alternator; 12 V starter with safety interlock	
Drive Train		
Manual Transmission	Five speed manual transmission with low-low (creeper) first gear; synchronised in all forward gears; two speed rear axle	
Clutch	180 mm (7.1 in.) single disc and pressure plate	
Differential Lock	Electric differential lock on rear axle with momentary engagement switch on dash	
Speeds	Maximum speed of 37.0 kph (23 mph) Optional 5th gear lock out available	Maximum speed of 33.8 kph (21 mph) Optional 5th gear lock out available
Tyres, Brakes and Steering		
Front Tyres	23 x 10.5 - 14 6-ply Ribbed (2WD)	23 x 10.5 - 14 6-ply Treaded (4WD)
Rear Tyres	26 x 12 - 14 6-ply Ultra Chevron tread	
Brakes	Service brakes: Heavy duty hydraulic four wheel disk brakes with 272 mm (10.7 in.) disk. Parking Brake: Hand lever actuated disk brakes on rear wheels.	
Steering	Hydrostatic Power Steering	
Front Suspension	Solid axle with heavy duty multiple leaf springs and shock absorbers	
Rear Suspension	Solid axle with heavy duty multiple leaf springs and shock absorbers	
Turning radius 2WD	71 cm (28 in.)	
Turning radius 4WD	203 cm (80 in.)	
Weight and Dimensions		
Maximum Capacity	1614 kg (3,550 lbs.) Maximum capacity. Available payload capacity includes weight of driver, passenger, added accessories	
Weight (without accessories)	2WD 881 kg (1,943 lbs) 4WD 998 kg (2,201 lbs)	2WD 893 kg (1,969 lbs) 4WD 1,010 kg (2,227 lbs)
Weight (with typical loadbed)	2WD 119 kg (2,466 lbs) 4WD 1236 kg (2,724 lbs)	2WD 1,131 kg (2,492 lbs) 4WD 1,248 kg (2,750 lbs)
Length	3.35 m (132 in.) without box; 3.45 m (136 in) with box	
Height	1.98 m (78 in.)	
Wheelbase	1.65 m (65 in.)	
Width	1.65 m (65 in.)	

\*Engine horsepower is provided by engine manufacturer. Actual operating power output may vary due to conditions of specific use.  
NOTE: Specifications, while correct at time of printing, may change without notice.



# Heavy Duty Utility Vehicle

# TRUCKSTER XD™



Kubota

The all new Truckster XD™ by Jacobsen is a true heavy duty utility vehicle. The Truckster XD has the largest standard payload capacity, a rugged and durable box made from thick 12 gauge steel, and is paired with the most powerful petrol and diesel Kubota engines available. The all-new Jacobsen Truckster XD is designed to make your toughest jobs easier.

## QUICK SPECS

**Engine:** Petrol 24.2 kW (32.5 HP)  
70 Nm (51.6 ft-lbs)  
Diesel 18.5 kW (24.8 HP)  
71.5 Nm (52.7 ft-lbs)

**Payload Capacity:** 1,610 kg (3,550 lbs.)

**Drive Train:** Five speed manual transmission  
Two speed rear axle with locking differential  
2WD or 4WD

**Speed:** Petrol 37.0 kph (23 mph)  
Diesel 33.8 kph (21 mph)

**Dimensions:**  
Length 3.35 m (132 in.) without box  
3.45 m (136 in.) with box  
Height 1.98 m (78 in.)  
Width 1.65 m (65 in.)



# TRUCKSTER XD™

## PRODUCT CONFIGURATION

- **Highest Standard payload** of 1,610 kg (3,550 lbs.). The largest payload capacity makes quick work of your biggest jobs since fewer trips are required. Heavy duty rear differential was custom designed for the Truckster XD™.
- **Toughest box** is built using the heaviest gauge steel of any box, up to 75% thicker than comparable boxes and has 20% more volume. Rugged tailgate and latch with easy slam shut function. Built-in stake pockets and multiple tie down points create a box with the versatility to tackle all the jobs you expect from a heavy duty utility vehicle.
- **Powerful Kubota engines with the highest HP and torque available** – Both the petrol and diesel engines have the highest torque available of any heavy duty utility vehicle (71.67 Nm (52.7 ft-lbs) diesel and 70 Nm (51.6 ft-lbs) petrol). The high torque allows effortless hauling of the heaviest loads and towing up to 907 kg (2,200 lbs) without trailer brakes 1,587 kg (3,500 lbs) with trailer brakes).
- **Industry's roomiest operator platform** with more space for operators and well-organised controls within easy reach. The optional suspension seat provides increased operator comfort for everyday operation and for longer tasks such as topdressing or spraying.
- **Highest approach angle** allows easy operation in the most undulated turf conditions.



### EQUIPPED STANDARD

- ✓ Liquid cooled engine (petrol and diesel)
- ✓ Five speed manual transmission
- ✓ Two speed rear axle
- ✓ Locking differential
- ✓ Four wheel hydraulic disk brakes
- ✓ Two Post ROPS with seat belts
- ✓ Tool-less radiator access
- ✓ Turf treads on rear tyres
- ✓ Hydraulic powered lift lower cylinder
- ✓ Hydraulic power steering
- ✓ Sliding adjustable seat
- ✓ Center console storage
- ✓ Glove box
- ✓ Phone / cup holder
- ✓ 12V power outlet
- ✓ Headlights
- ✓ Horn
- ✓ Radio holder

### ACCESSORIES

- 1.6 m (66") box
- 5 cm (2") Receiver hitch
- Canopy (two or four post ROPS)
- Four post ROPS
- Premium suspension seat (operator and passenger)
- Hi/Lo hydraulics with remote ports
- Hydraulic PTO
- Throttle control
- Turn signals
- Cab (roof, windshield, wiper, rear window)
- Doors
- Heater
- Auto tailgate
- Fifth wheel ball hitch including electric brake controller
- Core Harvester
- Top Dresser 1500
- Vicon Spreader
- Quick Aerator
- Implement Lift
- Mirrors, left and right
- Windshield for four post ROPS
- Storage accessory
- Work Light kit
- Reversing alarm
- Exhaust spark arrestor
- Fifth gear lock out

### AVAILABLE MODELS

- Petrol with Manual Transmission 2WD
- Petrol with Manual Transmission 4WD
- Diesel with Manual Transmission 2WD
- Diesel with Manual Transmission 4WD



**Tool-less access to the radiator** and optional hydraulic oil cooler for easy cleaning



**Steel hydraulic tubes** used to reduce risk of hydraulic leaks and reduce maintenance



**Robust axle mounted hitch** with 272 kg (600 lbs) tongue weight and 907 kg (2,200 lbs.) towing capacity (1587 kg (3,500 lbs) with trailer brakes)



Factory-filled with GreensCare™  
Biodegradable Hydraulic Fluid