

Drum Screen SST 518



Applications

The screening solutions of the Doppstadt SM series screen waste and raw materials such as compost, soil, construction waste, domestic waste, industrial waste, plastic, glass, paper, wood, biomass, sand, gravel, scrap or slag. The screens are perfectly suited for combined applications e.g. together with Doppstadt shredders or windsifters.

Advantages

- Very robust frame construction based on thick-walled profile tubes
- Speed-controlled direct drive with standard gear motor, therefore perfectly adjustable to screening process and quality requirements
- High screening throughput thanks to guided material processing inside the drum
- Wide range of possible applications thanks to combinable lower belts and the option of various mesh sizes
- Encased machine housing for zero-emission operation in connection with attachable exhaust device



Dimensions

| Chassis | Static |
|-------------------|--------|
| Total weight (kg) | 8100 |
| Length (mm) | 6863 |
| Width (mm) | 2450 |
| Height (mm) | 3188 |

Drive

Engine type Make Motor power (kW / PS) Electrical Three-Phase Motor 11 /

Screen drum

| Diameter (mm) | 1800 |
|---------------------|----------|
| Length (mm) | 4700 |
| Mesh size (mm) | bauseits |
| Mesh type | bauseits |
| Drum speed (min-1) | bauseits |
| Screening area (m²) | bauseits |

WWW.DOPPSTADT.COM Subject to technical changes - Specifications may be deviate