

SK600 MINI SKID STEER

 **Ditch Witch®**



MINI SKID STEERS

SK600 MINI SKID STEER



2 Industry-leading power to the attachment for improved strength and performance.

3 Efficient, low-maintenance Kubota® diesel engine provides outstanding power for all machine functions—24.8 hp (18.5 kW).

1 Advanced attachment latching system for more simple and secure connections.

4 Customer-driven control placement for optimized comfort and efficiency; the ergonomic operator's station has standard dual-lever ground drive controls, with an optional single-lever joystick available.

5 Two-way auxiliary control foot pedal enables you to maintain hydraulic flow to the attachment, freeing up your hands to control depth and ground speed.

6 Includes optimized hydraulics that deliver a smoother ride for enhanced operator comfort and productivity.

7 Best-in-class operator platform design gives more ground clearance than the competition and improves operator comfort and durability

8 Low-maintenance track tensioning allows easy track adjustment, giving your machine a longer lifespan and minimizing downtime.

9 Comes standard with 7-inch (180-mm) narrow tracks for 33.5-inch (850-mm) operational width for use in confined spaces.

10 600-lb (272-kg) rated operating capacity and an 76-inch (1.93-m) hinge-pin height enables productive loading and ability to handle tasks requiring more strength and power.



The Ditch Witch® SK600 is a construction-grade mini skid steer perfect for a variety of jobs like landscaping and irrigation. This compact machine is ideal for the most challenging jobs in hard-to-reach spots. From its narrow footprint to its class-leading power to the attachment, the SK600 is engineered to deliver more productivity and performance in a more compact package.

WE'RE IN THIS TOGETHER.





SK600 ATTACHMENTS

The Ditch Witch® organization offers a full line of quick-change attachments compatible with the SK600 Mini Skid Steer. Visit the SK600 product page on ditchwitch.com to use our interactive attachment selector, or ask your Ditch Witch dealer about additional attachment options.

SK600 MINI SKID STEER SPECIFICATIONS

	U.S.	METRIC
DIMENSIONS (STD)		
Operating height, max std. bucket	103 in	2.63 m
Overall height of machine	54 in	1.39 m
Overall length of machine, std. bucket	105 in	2.67 m
Overall length of loader, no attachment	80 in	2.14 m
Hinge pin height, max	76 in	1.93 m
Wheelbase/track length	36 in	925 mm
Machine width	33.5 in	850 mm
Ground clearance, min		
Center	8.5 in	216 mm
Side	4 in	102 mm
Machine weight (no attachment, fluids full)	2,418 lb	1096 kg
Operating capacity		
35% of tipping capacity	600 lb	272 kg
Tipping capacity	1,725 lb	782 kg
Angle of departure	27°	

POWER		
Engine	Kubota® D902-E4B	
Fuel	Diesel	
Gross power rating (SAE J1995)	24.8 hp	18.5 kW
Emissions compliance	EPA Tier 4	EU Stage IIIA
Number of cylinders	3	
Displacement	54.8 in³	0.898 L
Bore	2.83 in	72 mm
Stroke	2.9 in	73.6 mm
Rated speed	3,600 rpm	

OPERATION		
Ground drive speed		
Forward/reverse	4.1 mph	6.6 km/h
Ground pressure* (ISO/CD 16754)		
7-in (180-mm) tracks	4.8 psi	0.33 bar

HYDRAULIC SYSTEM		
Auxiliary circuit		
Double gear pump		
Flow rate (pump #1)	6.0 gpm	22.7 l/min
Flow rate (pump #2)	6.0 gpm	22.7 l/min
Pressure	3,000 psi	207 bar
Dual hydrostatic ground drive pumps		
Flow rate	12.5 gpm	47.2 l/min
Pressure	3,625 psi	250 bar

FLUID CAPACITIES		
Fuel tank capacity	10.5 gal	40 L
Engine oil, w/filter	5 qt	4.7 L
Hydraulic reservoir capacity	9.2 gal	35 L

NOISE LEVEL		
Sound pressure (operator ear)	90 dBA	
Sound power	104 dBA	

BATTERY		
SAE reserve capacity rating	110 min	
SAE cold crank @ 0°F (-18°C)	800 amps	
Electrical system	12V	

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.