



TTR

The **30** series

4400 HST (model with roll bar)



4400

Chassis	ACTIO™ – Full chassis with oscillation • Front steering • 4 equal wheel drive • RGS™ Reversibility			
Engine Type	Direct injection diesel			
Cylinders	3			
Output kW/HP (97/68/CE)	28/38			
Max engine rpm	3000			
Cooling system	Water			
Fuel tank capacity (lit./gal)	35/7.7			
Transmission	Hydrostatic – Mechanical selector with 3 speed range: low/normal/high Stepless speed variator in both forward and reverse gears from 0 to 6 Km/h in the “low” range, from 0 to 12,5 Km/h in the “normal” range, from 0 to 27 Km/h in the “high” range with a “Speed-fix” selector for maintaining pre-set speeds			
Power take-off	Independent PTO with 2 speeds 540 and 1000 rpm - (opt.) Front PTO 1000 rpm			
Hydraulic power lift	3-point hitch Cat. 1 - (Opt.) Front power lift with quick couplings			
Capacity (N/kp - N/lbs)	8330/850 - 8330/1870			
Steering	Hydrostatic with “Load Sensing” system			
Brakes	Rear-axle and parking brakes			
Tyres:	6.50-16	7.50-16	29x12.50-15 STG	29x12.50-15 GARDEN
Min. outer width (mm/in)	1125/44.3	1165/45.8	1380/54.3	1380/54.3
Ground clearance (mm/in)	260/10.2	275/10.8	255/10.0	255/10.0
Weight (kg/lbs)	1110/2447			
Standard equipment	Rotating “Control mechanism” for immediate and automatic reversibility of the driving position • Front and rear differential lock • Disengaging rear drive wheels • Safety roll bar • Sprung, adjustable “SC” seat • Power-lift up/down control valve			
Dimensions:				
Wheel base (mm/in)	1300/51.2			
Lenght (mm/in)	3110/122.4			
Height (mm/in)	2010÷2040 / 79.1÷80.3			