

XLS - Single disc centrifugal salt spreader / Working width from 6 to 18 m

Models	Capacity (l)	Maximum load (kg)	Weight (kg)	Length (cm)	Width (cm)	Height (cm)
XLS 300	250	550	64	118	113	104
XLS 500	350	550	68	124	123	114

All models are equipped with: Plastic hopper and stainless steel bottom – Stainless steel spreading disc – Standard filtering grid – PTO shaft

OPTIONALS: Hopper tarpaulin cover – Articulated agitator – Stainless steel salt/sand guard – Mechanical remote control (length = 2,5 m) – Single acting hydraulic control

XTL - Pull type single disc salt distributor / Working width from 6 to 14 m

Models	Capacity (l)	Maximum load (kg)	Weight (kg)	Length (cm)	Width (cm)	Height (cm)
XTL 300 (*)	250	400	108	192	160	140

(*) Not homologated for road use (maximum transport speed 20 km/h, maximum working speed 14 km/h)

All models are equipped with: Plastic hopper and stainless steel bottom – Stainless steel spreading disc – Wheels 18×8,50-8 GARDEN S365 – Clevis hitch

OPTIONALS: Towing eye – Trailer hitch coupling – Hopper tarpaulin cover – Articulated agitator + Standard filtering grid – Stainless steel salt/sand guard – Mechanical remote control (length = 2,5 m) – Single acting hydraulic control – Tail lights – Flashing light – 17×8,00-8 TMH tyres



Mod. XLS



Mod. XTL

OPTIONS – XLS - XTL

	Hopper tarpaulin cover
	Articulated agitator
	Stainless steel salt/sand guard
	Mechanical remote control (length = 2,5 m)
	Single acting hydraulic control

OPTIONS – XTL

	Towing eye
	Trailer hitch coupling
	Trailer rear lights
	Flashing light
	17×8,00-8 TMH tyres

