

Technical data

Dimensions

Length excl. towing eyelet 4.150 mm Length incl. towing eyelet 4.615 mm Width excl. side brushes 1.900 mm Heiaht 2.260 mm Service weight approx. 3.180 kg Gross weight, admissible 8.000 kg Pay load approx. 4.820 kg Sweeping width 2.200 - 2.700 mm

Dirt hopper

Capacity Dumping height Dumping position Warning signal by dumping Manual input

Tyres

Parking support leg

Adjustable in height

Elevator

Hydraulic driven Separate raise/lowering of elevator

Wheel axle

Trailer axle equipped with leaf spring assembly and rubber springs Admissible load: 7000 kg

Option:

- breaking-up attachment, right side
- Hydraulic high pressure (170 Bar) washing unit incl. hose reel with 13 m hose and high pressure gun fittings
- For the environmentally conscious the machine can be equipped with a PM10 suction system which maximizes the removal of fine dust
- Central lubrication system
- Side displacement of the draw bar
- Hydraulically adjustable sweeping width "side shift"
- Tilting angle adjustment of right side brush

Beacon light

1 pcs, rear left

Broom flexibility Automatically floating broom suspensions

Power requirements

Towing vehicle with 540 rpm type P.T.O. min. 48 kW (65 hp)

Hydraulic

Hydraulic motors: Orbit motors 315 cc Hydraulic oil cooler Hydraulic pump with gear box Hydraulic oil tank: capacity 160 l

225/75 R 17,5" Brake system

Single hose air brake system with drum brakes

Remote control

Electrically controlled proportional valves Individual speed control from driver's cab for the side brushes, roller brush and elevator

Sprinkler system

Water tank capacity: 1100 l Water tank in stainless steel Level indicator, remote controlled

Water pump: hydraulic driven 2-cylinder membrane pump, pressure 6 Bar, capacity 26 l/min

Central cleaning system

for the hopper and elevator

Sweeping speed: 1-20 km/h

Transport speed admissible: 40 km/h

Safety

(F Conforms to safety EN ISO 12100-1:2005, EN ISO 12100-2:2005, EN 982+A1:2008

Fine dust control PM10 Certified

Subject to alterations of specifications and equipment details.

3.100 | 2.640 mm rear acoustic left and right