





2.2

<http://tiny.cc/multione2-2EN>


 LIFT CAPACITY 450 kg	 ENGINE POWER 22 hp	 SPEED 12 km/h	 FLOW RATE 31 l/min	 LIFT HEIGHT 1,82 m
--	--	---	--	--

Tires size	Width
20x8.00-10	980 mm (38.6 in)
21x8.00-10	998 mm (39.3 in)
23x8.50-12	1020 mm (40.2 in)

Model	2.2
Engine	B&S Vanguard 7220
Power (Iso Gross)	22 HP / 17 kW
Fuel	Petrol
Transmission	Hydrostatic
Drive speed (max.)	12 km/h (7.5 mph)
Aux. hydraulics oil flow	31 l/min (8.2 gal/min)
Max. lifting height	1,82 m (71.7 in)
Max. lifting capacity (w/backweights)	450 kg (992 lbs)
Breakout force / 50 cm (19.7 in)	500 kg (1102 lbs)
Pushing force (c)	800 kgf (800 kp)
Specific ground pressure (w/standard tires)	593 kg/m ² (1307 lbs/sqft)
Turning radius: inside/outside	700 / 1698 mm (27.6 / 66.9 in)
Standard tires (Tractor profile)	21x8.00-10
Length	1859 mm (73.2 in)
Height	1900 mm (74.8 in)
Weight	680 kg (1500 lbs)
Product Code	C951021
Price	Get a Quote



2.2 FEATURES AND OPTIONS

- 4WD hydrostatic Direct Drive motors, proportional servo
- DBS (Dynamic Block System)
- Hydraulic oil cooler
- Hydraulic multiconnector
- Self-levelling H-frame boom
- 4-functions joystick
- ROPS-FOPS Level I
- 2 front working light
- Ergonomic seat with armrests and safety belt, adjustable position
- Mechanical parking brake

Options	Code	Price
Luxury cab (glass) with heating system	C885224	Get a Quote
Smart cabin with heating system	C885233	Get a Quote
Road lights, LED	C885229	Get a Quote
Additional working lights, LED, set of 3	C885230	Get a Quote
Trailer coupling	C880235	Get a Quote
Turf profile tires 20x8.00-10, set of 4	C885211	Get a Quote
Additional backweights 84 kg (185 lbs)	C880234	Get a Quote
Heated seat	C885225	Get a Quote
Driver area cover	C880049	Get a Quote
Left protection bar for operator	C885027	Get a Quote
Back up alarm	C883021	Get a Quote