

Grinder AK 635 SA



Applications

The grinders of the DOPPSTADT AK series process green waste, yard waste, biowaste, pre-shredded logs and roots, waste wood and wooden pallets. For special applications, the AK grinders can be combined with other Doppstadt products, such as shredders, screening machines or beet washers (e.g. for the pulping of beets).

Advantages

- Continuous grinding with maximum performance by means of load sensing material in-feed
- 6 m feeding hopper and 7 m long discharge conveyor
- Contaminant resistant thanks to free-swinging flails
- Easy one-man operation
- Large protection doors on either side and centralized lubrication points for easy maintenance

Dimensions

Chassis Semi-trailer Total weight (kg) 30000 Length (mm) 17200 Width (mm) 2500 4500 Height (mm) Transport width (mm) 2500 3930 Transport height (mm) Transport length (mm) 12410

Drive

Engine type diesel engine

Make Mercedes-Benz OM 502 LA

Exhaust level EUROMOT III B
Motor power (kW / PS) 440 / 598
Fuel tank (l) 900

Torque (Nm) 2800 Nm at 1300 rpm

Discharge conveyor rear

 Width (mm)
 1500

 Length (mm)
 7000

 Belt speed (m/s)
 2

Flail drum

 Width (mm)
 1750

 Diameter (mm)
 1100

Speed (min-1) 970 - 1140 rpm (depending on engine

speed)

Number of Flail teeth 36



