

Shredder-Grinder DZ 750



Applications

The DOPPSTADT DZ 750 shreds waste wood, roots, green waste, bulky logs and much more. The installation of two coordinated components on one chassis offers an optimum solution on site for challenging shredding tasks.

Advantages

- Shredding and grinding in one machine
- Production of finished goods in one machine
- Easy one-man operation
- Contaminant-resistant high-speed shredding
- Metal separation by two overband magnets (additional magnet optionally available)

Dimensions

Chassis	Semi-trailer
Total weight (kg)	46000
Length (mm)	18516
Width (mm)	2550
Height (mm)	4100
Transport width (mm)	2550
Transport height (mm)	3980
Transport length (mm)	13550

Drive

Engine type	Volvo diesel engine
Make	Volvo TAD 1643 VE
Exhaust level	EUROMOT TIER IV
Motor power (kW / PS)	565 / 768
Fuel tank (I)	900
Torque (Nm)	3261

Discharge conveyor rear

Vidth (mm)	1500
ength (mm)	6000

Flail drum

Width (mm)	1750
ength (mm)	1100
Speed (min-1)	1080
Number of Flail teeth	36

Roller

Number of rollers	1
Roller Length (mm)	3000
Roller Diameter (mm)	600
Roller Speed (min-1)	20 - 25
Number of roller teeth	21/42
Loading height (mm)	3000



