



# Leader

505 | 655















 **ROBUSTA PER USO SEMIPROFESSIONALE CON ATTACCO PRIMO BRACCIO LATERALE PER MAGGIORE PROFONDITÀ, E DISTANZA LATERALE. ROTAZIONE IDRAULICA DI SICUREZZA 105°.**

 **STRONG FOR SEMIPROFESSIONAL WORK WITH FITTING OF THE MAIN ARM SIDEWISE FOR MAJOR DEPTH AND DISTANCE. SAFETY DEVICE: HYDRAULIC ROTATION 105°.**

 **SOLIDE POUR UTILISATION DEMI-PROFESSIONNELLE AVEC ATTACHE DU 1<sup>ER</sup> BRAS SUR MACHINE POUR UNE PORTÉE TRÈS IMPORTANT. SÉCURITÉ: ROTATION HYDRAULIQUE (BALAYAGE) 105°.**

 **STARK FÜR HALBPROFI-ARBEIT MIT SEITLICHE HAUPTARM-EINSATZ FÜR GRÖßERE TIEFE UND ENTFERNUNG. HYDRAULISCHER SICHERHEITSWINKEL 105°.**

 **ROBUSTA PARA TRABAJOS SEMIPROFESIONAL CAN ENGANCHE PRIMER BRAZO LATERAL PARA MAJOR PROFUNDIDAD Y DISTANCIA. SEGURIDAD CON ROTACION HYDRAULICA 105°.**

MODEL	 kg	 (HP/KW)	 cm	 r.p.m.	 Kg		 230°	 Lt.	 L / MIN	 (HP/KW)	 (r. p. m.)
LEADER 505	2500	50-37.5	200	540	1100	II	230°	155	84	50-37.5	3110
LEADER 655	3500	50-37.5	200	540	1170	II	230°	155	84	50-37.5	3110



\*\*\*\*\*  
**3 ANNI DI GARANZIA**  
\*\*\*\*\*

SUI PARTICOLARI IN FUSIONE

 3 YEARS WARRANTY ON CAST METAL PARTS

 3 ANS DE GARANTIE SUR LES PIÈCES MOULÉES EN FONTE ACIÉRÉE

 3 JAHRE GARANTIE AUF GUSSTEILE

 GARANTÍA DE 3 AÑOS EN PIEZAS DE FUNDICION





- **BASAMENTO E COLONNA IN FUSIONE**
- **FRAME AND COLUMN IN CAST METAL**
- **CHASSIS ET COLONNE MOULÉS EN FONTE ACIERÉ**
- **RAHMEN UND SÄULE AUS GUSSMETALL**
- **BASTIDOR Y COLUMNA DE FUNDICION**



- **POMPA E MOTORE IN GHISA**
- **CAST IRON ENGINE AND PUMP**
- **POMPE ET MOTEUR EN FONTE**
- **MOTOR UND PUMPE AUS SPEZIALGUSS**
- **BOMBA Y MOTOR EN FUNDICION**



- **ROTAZIONE IDRAULICA DI SICUREZZA 105°**
- **SAFETY DEVICE: HYDRAULIC ROTATION 105°**
- **SÉCURITÉ: ROTATION HYDRAULIQUE (BALAYAGE) 105°**
- **HYDRAULISCHER SICHERHEITSWINKEL 105°**
- **SEGURIDAD CON ROTACION IDRAULICA 105°**



- **BIELLA PRIMARIA IN FUSIONE**
- **PRIMARY CONNECTING ROD IN CAST METAL**
- **TIGE PRINCIPALE MOULÉE EN FONTE ACIERÉ**
- **HAUPFPLEUEL AUS GUSSMETALL**
- **VASTAGO PRINCIPAL DE FUNDICION**



- **PARAURTI CON FANALERIA**
- **BUMBER WITH LIGHTS**
- **PARE-CHOC AVEC FEUX**
- **STOSSTANGE MIT LICHT**
- **BARRA CON LUCES**