



from 75 to 120 HP



Ø 20 cm max

FORESTRY MULCHER WITH FIXED TOOTH ROTOR FOR SKID STEERS.

Robust and compact, the UML/SSL is renowned for its ergonomic design that guarantees excellent visibility for the operator during various situations. Thanks to the diverter valve kit option, it can be utilized with any brand of skid steer on the market. The VT version with automatic variable displacement hydraulic motor increases productivity by up to 50% and simultaneously reduces fuel consumption.

STANDARD EQUIPMENT		
Enclosed machine body	Working pressure control gauge	
Belt transmission	Push frame	
Hydraulic piston motor 63cc with relief and anticavitation valve (UML/SSL) - (130 - 150 L/min)	Dual row protection chains	
110/60cc variable torque hydraulic piston motor (UML/SSL/VT) - (130 - 200 L/min)	Anti-dust rear hood	
Hydraulic hoses	Motor integrated into the frame	
Hydraulic hood	OPTIONS	
Adjustable skids	Customized setting hydraulic motor	
Welded counter blade	Diverter valve	
	Oil cooler kit	
	Multiple tooth options	
	Rotor Bite Limiter (UML/SSL/VT)	



THE STARTING POINT
FOR ANYONE WITH A SKID STEER

FEATURES

- Low profile frame design** for excellent working visibility
- Enclosed door drive** revolutionary system of door opening/ closing that prevents dirt from entering into the service areas of the machine
- Reinforced sides** Increases axial load bearing
- Heavy duty adjustable skids**
- Aggressive body design** the protruding rotor allows more material to process without dragging material
- External pressure control Gauge**
- Poly-Chain® Carbon transmission belts** for solid power conversion and maximum productivity
- Double row protection chains** knocks down the material exiting out the back, increasing safety

MAIN OPTIONS

- VT motor** adjusts the motor to obtain the maximum performance from any skid steer
- Diverter valve to control hood cylinders (plug & play)** to control the opening and closing of the hydraulic door
- Oil cooler kit** for working in hot climates
- Roof mounted cooler** for working in hot climates

MODEL	Engine (HP)		Flow rate (L/min)		Pressure (bar)		Working width (mm)	Total width (mm)	Weight (kg)	Max shredding diameter (mm)	No. teeth	
	min	max	min	max	min	max					C/3+C/3/SS	I+C/3/SS
UML/SSL 125	75	120	130	150	200	350	1340	1640	1140	200	26+2	36+2
UML/SSL 150	75	120	130	150	200	350	1580	1880	1240	200	32+2	42+2
UML/SSL 175	85	120	130	150	230	350	1820	2120	1330	200	36+2	50+2
UML/SSL/VT 125*	75	120	130	200	200	350	1340	1640	1100	200	26+2	36+2
UML/SSL/VT 150*	75	120	130	200	200	350	1580	1880	1250	200	32+2	42+2
UML/SSL/VT 175*	75	120	130	200	200	350	1820	2120	1340	200	36+2	50+2

Data refers to machine as standard. The technical data in this catalog may be altered without prior notice.
*Variable displacement hydraulic motor.